

Model	VQ-5MG-M/C16
Resolution (H × V)	2448 × 2056
Sensor	Sony ICX 625 AL/AQ
Sensor Size (Optical Format)	8.44 mm × 7.09 mm , 2/3"
Sensor Type	Progressive Scan Interline Transfer CCD
Pixel Size	3.45 μm × 3.45 μm
Sensor Output	2 Tap
Pixel Data Format	8 bit, 10 bit, 12 bit
Output Format	Mono : Mono8, Mono10, Mono10 packed, Mono12, Mono12 packed Color : Bayer BG8, Bayer BG12, Bayer BG12 packed
Interface	Gigabit Ethernet
Electronic Shutter	Global Shutter
Shutter Speed	39 μs ~ 7 s (10 μs step)
Partial Scan (Max. Speed)	41 fps at 256 Lines
Binning	×1, ×2, ×3, ×4 (Horizontal and Vertical Independent)
Lookup Table	G = 1.0, User defined LUT (Lookup Table)
Black Level	Adjustable (0 ~ 128 LSB at 12 bit, 256 steps)
Gain Control	Analog: ×1 ~ ×40 (0 ~ 32 dB)
Max. Frame Rate	16 fps
Exposure Mode	Timed, Trigger Width, Double Exposure
Dynamic Range	52 dB
Auto Control	Auto Gain, Auto Exposure, Auto White Balance
Dimension / Weight	C-mount : 35 mm × 35 mm × 59.7 mm , 83 g CS-mount : 35 mm × 35 mm × 54.7 mm , 81 g
Temperature	Operating: 0°C ~ 40°C, Storage: -40°C ~ 70°C
Lens Mount	C mount or CS mount
Power	Power over Ethernet (802.3af) or 8 ~ 38 V DC
API SDK	Vieworks Imaging Solution 6.X



1 : +12 V DC,
4 : I/O Output+
(HR10A-7R-6PB)

2 : Trigger IN+ 3 : Trigger IN-
5 : I/O Output-, 6 : DC Ground

