



The Os-series is a new digital high-speed camera designed to operate in the most demanding environments. The salient design feature of the Os 4 are its compact size combined with a wide data bus, making it capable of achieving very high frame rates (up to 6,000 fps) including transfer speeds to high-capacity solid-state (non-volatile) memory.

KEY FEATURES

| | |
|--|------------------------------|
| Maximum Resolution | 1024 x 1024 |
| Maximum FPS @ Maximum Resolution | 6,000 fps |
| Image Storage @ Max Frame Rate (DDR 8) | 6,218 |
| Image Storage @ Max Frame Rate (SSD 512) | 6,338 |
| Streaming FPS @ Max Resolution | 355 fps |
| Maximum FPS | 330,000 @ 1024 x 8 |
| Minimum Exposure Time | 1µs |
| Sensitivity ASA/ISO | 8000 ISO Mono 3000 ISO Color |
| Power Requirements | 18-36 VDC |
| Operating Temperature | -40+50°C / -40+122°F |

SENSOR

| | |
|---------------------|--------------------------|
| Sensor Type | CMOS - Proprietary |
| Sensor Size | 13.9 x 13.9 mm |
| Sensor Format | 1.3 inch |
| Pixel Size (micron) | 13.68x13.68 µm |
| Pixel Depth | 12 bit mono 36 bit color |

INPUTS

| | |
|---------|---|
| Trigger | TTL & Switch/Circular buffer with on-camera or software trigger |
| Sync | Phase-lock TTL |

OUTPUTS

| | |
|-------|---------------------|
| Sync | Frame sync / Strobe |
| HDSDI | Optional |

FEATURES

| | |
|--------------------------------|---|
| Approx. Size | 65 x 63 x 87 mm (W x H x L) |
| Approx. Weight | 0.69 kg or 1.52 lbs |
| Shock/Vibration Rating | Shock: 200G / Vibration: 40G - All axes |
| Battery Powered Operation Time | Optional |
| Mount | C-Mount standard , F Adaptor optional |

SOFTWARE

| | |
|-----------------------|--|
| Motion Studio | Windows 32/64 |
| Motion Inspector | Windows 32/64 - MAC OS X - Apple iOS |
| Plug-ins/SDK | SDK, LabVIEW™ or MatLab® |
| File Formats | Proprietary RAW |
| On-the-fly Conversion | TIF, BMP, JPG, PNG, AVI, MPG, TP2, MOV, MRF, MCF |

COMMUNICATION

| | |
|----------|-----------|
| Ethernet | 1000BaseT |
|----------|-----------|